4 x 4 Power	4 x 4 Marathon	Skellerup Boot Remover
FRF004-FRF013	FRF104-FRF113	FSC775
Mens 4–13	Mens 4–13	_
Calf	Knee	-
Moulded rubber	Moulded rubber	_
_	_	-
_	_	-
Rubber	Rubber	Polypropylene  Designed to help remove boots
Farming/hardwearing	Farming/hardwearing	Designed to help remove boots of all types
Removable orthotic	Removable orthotic	-
-	-	-
-	-	

Product code

Size

Height

Sole

Penetration resistant sole

Steel toe cap

Material

Used for

Innersole type

Temperature guide

Safety certification





## FOOTWEAR QUICK REFERENCE GUIDE

Skellerup Industries Ltd
0800 475 355   customer.services@skellerup.co.nz
skellerup.co.nz

	Quatro Light Knee	Quatro Insulated Knee	Quatro Insulated Calf	Quatro Insulated Comfort Plus	Quatro Safety Insulated Knee	Quatro Non Insulated Safety Knee
Product code	FRQ722–FRQ734	FRQ302-FRQ314	FRQ202-FRQ214	FRS503-FRS513	FQS606P-FQS613P	FQS706P-FQS714P
Size	Mens 2–14	Mens 2–14	Mens 2–14	Mens 3–13	Mens 6–13	Mens 6–14
Height	Knee (can trim to calf)	Knee	Calf	Calf	Knee	Knee (can trim to calf)
Sole	Moulded rubber	Moulded rubber	Moulded rubber	Moulded rubber	Nitrile rubber (oil, chemical & heat resistant)	Nitrile rubber (oil, chemical & heat resistant)
Penetration resistant sole	_	_	_	_	<b>✓</b>	<b>✓</b>
Steel toe cap	_	_	_	_	<b>✓</b>	~
Material	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
Used for	Farming	Farming/cold weather	Farming/cold weather	Adjustable fit - suitable for wider calf	Trades/farming	Trades/farming
Innersole type	Removable Quatro™ orthotic	Removable Quatro™ orthotic	Removable Quatro™ orthotic	Removable Quatro™ orthotic	Removable Quatro™ orthotic	Removable Quatro™ orthotic
Temperature guide	Warm weather	Fully insulated, rated to -50°C	Fully insulated, rated to -50°C	Fully insulated, rated to -50°C	Fully insulated, rated to -50°C	Warm weather
Safety certification	_	_	_	-	AS 2210.3:2019; SB P E CI HRO FO SRC	EN ISO 20345:2011; AS 2210.3:2019; SB, P, FO, E, HRO, SRC

	Red Band Men	Red Band Women/Youth	Red Band Children	Red Band Junior	Red Band Safety Knee	Quatro Dielectric Safety Knee
Product code	FRR104-FRR114	FRR203-FRR209	FRR009-FRR015	FRR003-FRR008	FRR504-FRR514	FQE404-FQE414
Size	Mens 4–14	Womens 3–9	Childrens 9–13, 1–2	Childrens 3–8	Mens 4–14	Mens 4–14
Height	Calf	Calf	Calf	Calf	Knee (can trim to calf)	Knee
Sole	Calendered rubber	Calendered rubber	Calendered rubber	Calendered rubber	Nitrile rubber (oil, chemical & heat resistant)	Nitrile rubber (oil, chemical & heat resistant)
Penetration resistant sole	-	-	-	-	-	-
Steel toe cap	_	-	_	_	<b>✓</b>	<b>✓</b>
Material	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
Used for	Everyday/wet weather	Everyday/wet weather	Everyday/wet weather	Everyday/wet weather	Trades/farming	Transmission/electrical
Innersole type	Rubber foam	Rubber foam	Rubber foam	Rubber foam	Removable orthotic	Removable Quatro™ orthotic
Temperature guide	-	-	-	-	-	-
Safety certification	_	-	_	_	AS 2210.3:2019; EN ISO 20345-2011; SB, FO, E, HRO, SRA	EN50321:2018; EN ISO 20345:2011; SB CI HRO SRC FO E Class 2 (AC 20 kV)
	Perth Men	Perth Women/Youth	Ashley	Ashley Safety	Schoen Forestry Pro	Schoen Forestry Pro Spiked
Product code	FRP124-FRP135	FRY143-FRY148	FRA155-FRA163	FRS525-FSA533	FSC856-FSC864	FSC956-FSC964
Size	Mens 4–15	Womens 3–8	Mens 5–13	Mens 5–13	Mens 6–14	Mens 6–14
Height	Knee	Knee	Calf	Calf	Knee	Knee
Sole	Calendered rubber	Calendered rubber	Calendered rubber	Nitrile rubber (oil, chemical & heat resistant)	Nitrile rubber (oil, chemical & heat resistant) Fire-retardant 360 Sure grip	Nitrile rubber (oil, chemical & heat resistant) Fire-retardant 360 Sure grip
Penetration resistant sole	_	_	_	_	-	-
Steel toe cap	_	_	_	~	<b>✓</b>	<b>✓</b>
Material	Rubber	Rubber	Rubber	Rubber	Rubber	Rubber
Used for	Everyday/wet weather	Everyday/wet weather	Tramping/wet weather	Safety/waterproof	Forestry	Forestry
Innersole type	Rubber foam	Rubber foam	Rubber foam	Rubber foam	Rubber foam	Rubber foam
Temperature guide	_	_	_	_	_	_
Safety	_	_	_	AS 2210.3:2019; SB, E, FO, HRO, SRA	Chainsaw protection Level 3 28m/s; EN ISO 20345- 2011; EN ISO 17249:2013; AS 2210.3:2019; SB, FO, E, HRO,SRA	Chainsaw protection Level 3 28m/s; EN ISO 20345-2011; EN ISO 17249:2013;